

Technical Specifications



APC Back-UPS 600, 230V without Auto Shutdown Software, India

BX600C-IN

Call for More Information 18001030011

- Includes: User manual, Warranty card

Output

Output power capacity	360 Watts / 600VA
Max Configurable Power (Watts)	360 Watts / 600VA
Nominal Output Voltage	230V
Output Frequency (sync to mains)	47 - 63 Hz Sync to mains
Topology	Line interactive
Waveform type	Stepped approximation to a sinewave
Output Connections	(3) India 2/3-pin 6A

Input

Nominal Input Voltage	230V
Input frequency	47 - 63 Hz
Input Connections	India 3-pin 6A
Cord Length	1.2meters
Input voltage range for main operations	145 - 290 V
Number of Power Cords	1

Batteries & Runtime

Battery type	Lead-acid battery
Typical recharge time	6hour(s)
Replacement Battery	APCRBC110 

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Communications & Management

Control panel	LED status display with on line : on battery : replace battery and building wiring fault
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rating	255Joules
---------------------	-----------

Physical

Maximum Height	218MM, 21.8CM
Maximum Width	107MM, 10.7CM
Maximum Depth	237MM, 23.7CM
Net Weight	4.7KG
Shipping weight	5.2KG
Shipping Height	295MM, 29.5CM
Shipping Width	165MM, 16.5CM
Shipping Depth	310MM, 31.0CM
Color	Black

Environmental

Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0 - 3048meters
Storage Temperature	-15 - 45 °C
Storage Elevation	0 - 15240meters
Audible noise at 1 meter from surface of unit	45.0dBA

Conformance

Approvals	BIS
Standard warranty	2 years repair or replace

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.