

Product datasheet

Specifications



Galaxy VX 500kVA, 400V, Start up 5x8

GVX500K500NHS

Overview

Presentation	A highly efficient, modular, 500 kVA 3-phase UPS that provides the performance, flexibility, and maximized asset utilization today's large data centers and mission critical applications require. This EcoStruxure connected UPS features up to 99% efficiency in eConversion mode. Includes 5x8 start-up service.
Lead time	Special Order - Call for Quoted Lead Times

Main

Main Input Voltage	400 V 3 phases
Other Input Voltage	380 V 415 V 440 V
Main Output Voltage	400 V 3 phases
Other Output Voltage	380 V 415 V 440 V
Rated power in W	500 kW
rated power in VA	500 kVA
Battery type	External battery system
Provided equipment	Installation guide Start-up service
Range of product	Galaxy VX
Range compatibility	Galaxy VX

Batteries & Runtime

Efficiency	View Efficiency Graph
Battery voltage	480 V
Discharge battery voltage	384 V DC
Battery power in VAh	0 VAh runtime
Extended runtime	0

General

Redundant	No
------------------	----

Physical

Colour	White
Height	197 cm

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Width	240 cm
Depth	90 cm
Net weight	2030 kg
USB compatible	No

Input

Network frequency	40...70 Hz
Maximum input current	851 A
Max short time withstand current	100 kA
Input harmonic distortion	Less than 3 % for full load
Load power factor	From 0.7 leading to 0.5 lagging without any derating

Output

Maximum configurable power in W	500 kW
Output frequency	50 Hz sync to mains 60 Hz sync to mains 50 Hz +/- 0.1 % for 50 Hz nominal unsynchronised
Crest factor	3 with THC <5%
Wave type	Sine wave
Output harmonic distortion	< 2% linear load and < 3% non-linear load
Output overload operation	10 minutes at 125% and 60 seconds at 150%
Maximum configurable power in VA	500 kVA

Conformance

Product certifications	cUL listed C-Tick CE UL 1778 5th edition
Standards	IBC 2012 IEC 62040-1-1 IEC 62040-2 IEC 62040-3 IEC 62040-4 ISTA 2B

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3333 ft
Ambient air temperature for storage	-15...40 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0.0000000000...15240.0000000000 m
Acoustic level	69.5 dBA
Heat dissipation	80387 Btu/h
IP degree of protection	IP20

Communications & Management

Free slots	2
------------	---

control panel	7" touch screen display
---------------	-------------------------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	215 cm
------------------	--------

Package 1 Width	106 cm
-----------------	--------

Package 1 Length	317 cm
------------------	--------

Package 1 Weight	2592 kg
------------------	---------

Contractual warranty

Warranty	1 year on-site repair or replace with factory authorized Start-Up
----------	---



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) **638403**

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard **Yes**

Packaging without single use plastic **No**

[EU RoHS Directive](#) **Compliant with Exemptions**

SCIP Number **7547f066-9302-46d9-96e9-461928dd6901**

REACH Regulation [REACH Declaration](#)

Use Again

Repack and remanufacture

Circularity Profile [End of Life Information](#)

Take-back **No**

WEEE  **The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins**

Image of product / Alternate images

Alternative



